

## IHS320X 2D BARCODE SCANNER



## **PRODUCT FEATURES**

- New decoding chip, interpret all kinds of 1D and 2D bar codes.
- Professional technology.
- Plug and Play, easy to set up and quickly match.
- Support lightning invoicing.
- Longer service life of the wire.

## SPECIFICATION

Light Source	617nm, LED Aimer, White LED		
Supported Symbologies	<ul> <li>1D: Codabar, Code11, Code39, Code93, UPC/EAN, Code128, EAN-128, Interleaved 2 of 5, Matrix 2 of 5, MSI code, Industrial 2 of 5, GS1 Databar.</li> <li>2D: QR Code, Data Matrix, PDF417, Invoice QR code</li> </ul>		
Scan Type	Image CMOS		
Scan Rate	30 frames / Sec.		
Scan Mode	Manual/Continuous/Automatic Induction Scanning		
Resolution / Precision	<b>1</b> <i>D</i> : ≥5 mil <b>2</b> <i>D</i> : ≥10 mil		
Typical depth of field	60 - 250 mm		
Scan Angle	Yaw: ±65°, Rotation: 360°, Pitch: ±60°		
Interface	USB-HID, RS232		
Symbol Contrast	25%		
Notification	LED Indicator and Buzzer		
Input Voltage	DC5V±5%		
Current	135mA		
Shock Resistance	Withstand multiple times 3m drop to concrete		





Operating Temperature	-20° C ~ 60° C
Storage Temperature	-40° C ~ 70° C
Humidity	5% ~95% RH(Non-condensing)

MECHNAICAL		
	Dimensions	175 mm x 65 mm x 72.5 mm
	Weight	185 g
	Material	ABS + PC

APPLICATION		CERTIFICATION	
	<ul><li>Super Markets</li><li>Shops</li><li>Warehousing</li></ul>		• CE • ROHS

**CAUTION!** : LASER RADIATION - DO NOT STARE INTO BEAM.

For more information, please contact your local Honeywell representative, or write to impact.sps@honeywell.com

Honeywell International India Pvt. Ltd. 1120-21, 11th Floor, Tower A, DLF Tower, Jasola, Jasola District Centre New Delhi - 110025, India https://impactbyhoneywell.com

