

COMPACT & RELIABLE PRINTER **WITH IMPACT PLUG & PLAY** **TECHNOLOGY**

IH-2

4-inch Desktop Printer **FOR LIGHT WEIGHT** **APPLICATIONS**

Quiet, reliable operation and an intuitive design makes IH-2 desktop printer the right fit for light-duty labelling applications in a variety of industries.



Easy to Install. Ready to Use



- USB, serial & in-built ethernet
- Exceptionally compact design
- Intuitive design
- Compatible with ribbon lengths up to 300 m (984 ft)

Improve Productivity With Latest Technology

- Supports thermal transfer/direct thermal printing method
- Print speed up to 127 mm/s (5 inch/s) Max
- Print resolution 203dpi (8 dots/mm)
- Advanced detection capabilities like adjustable reflective sensor, fixed transmissive sensor (central aligned), head-up sensor, ribbon end sensor
- Features bi-colour status led displaying status & control key for ease of use
- Supports ZPL & TSPL

Features & Benefits



An economical solution for light-duty thermal printing applications.



32 MB of RAM & 16 MB of flash memory for improved productivity.



Industry-standard connectivity includes USB host and device, and options for Ethernet and serial communications.



Easy to use, with a quick-opening design for media replenishment.



Supports TSPL, ZPL print languages for maximum compatibility.

Contact Honeywell Support Team

1800 890 7447

For Support Related Queries

IH-2 Desktop Label Printer

Specifications	
Printing	Printing Method :Thermal Transfer/ Direct Thermal
	Resolution :203dpi (8 Dots/Mm)
	Printing Speed :127 mm/s (5 inch/s) Max
	Printing Width :108 mm max. Printing Length :15-200mm
Processor	NUC976
Memory	RAM :32MB Flash :16MB
Detection	Adjustable Reflective Sensor, Fixed Transmissive Sensor (Central Aligned), Head-Up Sensor, Ribbon End Sensor
Media	Types : Roll-Fed Or Fan-Fed, Die-Cut Or Continuous Label, Tag Stock, Continuous Receipt Paper
	Width :0.79"(20mm)-4.65" (118mm) Thickness :0.003" (80um) - 0.007" (180um)
	Label Roll Diameter :5"(127 mm) Core Diameter :1"(25.4mm), 1.5" (38mm), 3" (76.2 mm)
Ribbon	Types :Wax, Wax / Resin, Width :1.33"(33.8mm)- 4.33"(110mm)
	Length :984' (300m) Core Diameter :1"(25.4mm)
Programming Language	TSPL, ZPL
Software	Label Design :BarTender Ultralite Seagull Driver Windows 2000, Vista, 7, 8, 10
Resident Fonts	Bitmap Fonts :Fonts Size - 0-8 / Fonts Type -A-H, O, GS, P-V Fonts Rotation - 90°, 180°, 270°, 10 Times Maximum Expandable In Horizontal And Vertical Directions.
	TTF Fonts :Monotype CG Triumvirate™ Scalable True Type Font
Download Fonts	Bitmap Fonts :Fonts Rotation - 90°, 180°, 270° Single Characters Rotation - 90°, 180°, 270°
	Asian Fonts :16x16, 24x24, Euro English, US English, Many More Universal Font
Code Pages	dos437, 720,737, 755, 775, 850, 852, 855,856, 857, 858, 860, 862, 863, 864, 865, 866, windows 1250, 1251, 1252, 1253, 1254, 1255, 1256, 1257, 1258 iso8859-1, -2, -3, -4, -5, -6, -8, -9, -15 dbcs 932 uis, 936 (gbk), 949 (koran), 950 (big5)
Barcode	1D :Code 39, Code 93, Code 128UCC, Code 128 Subset A, B, C, Codabar, Interleave 2 Of 5, EAN-8, EAN-13, EAN-128, UPC-A UPC-E, EAN And UPC 2 (5) Digits Add-On, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11
	2D :PDF417, Maxicode, DataMatrix QR Code, Aztec
Interfaces	Standard :USB, RS232, Ethernet
Control Panel	Two Bi-Color Status LEDs :Ready,Status Control Key :Feed
Power	AC/DC Switching Power Adapter I/P: AC100-240V, 50/60Hz, O/P: DC 24V/2.5A
Environment	Operation :5° To, 40°, 30% - 85%, Non - Condensing
	Storage :20° To 50°, 10% - 90%, Non - Condensing

Overview	
Model Name	IH-2
Material	ABS
Weight	2.26 Kg, Excluding Consumables
Dimensions	289x 232x 192 mm (LxWxH)
Application	SME's

Options And Accessories
External Label Roll Holder For 8" (203mm) OD Label Rolls Cutter Module Peeler Module

Agency Approvals
CE BIS

Honeywell International India Pvt. Ltd.
Honeywell International Safety India

1120-21, 11th Floor, Tower A, DLF
Tower, Jasola, Jasola District Centre
New Delhi - 110025, India

www.impactbyhoneywell.com
Toll Free Number : 1800 890 7447

For More Information, Please Contact Your
Local **Honeywell Representative**, Or Write To
impact.sps@honeywell.com